

GLASSWASHERS

TECHNICAL DATA

695 mm

265 mm

500 mm

845 - 895 mm

Height

Cabinet

Width

Cabinet

Depth

Cabinet inc. legs

Usable Wash

NORRIS GLASSMATE RINSE TANK SERVICE ACCESS 295 0 -110-505 -50 to wall **PLAN** 265 LOADING 32mm drain 700 0 ... 0 - Norms 390 540 TO LOAD HEIGHT 145 90 425-450 150 to 175 180 SIDE ELEVATION FRONT ELEVATION

The Glassmate is a tough and reliable glasswasher manufactured to operate under the most demanding conditions. With an optional cooling cycle designed to minimise the turnaround of glassware, this machine will prove to be reliable and dependable in the busiest of work environments. 10amp version available.

FEATURES

- Warranty: 2 years parts and labour, 5 years on the cabir
- Co
- Cle
- 30
- Au an
- Sel
- Sui
- Rir the
- Ad
- Sir
- Do
- Hic
- Au:

INC

- 1 x
- 2 x
- 1 x
- 1 x (

abinet	Cabinet With door open	550 mm 830 mm
compact size suited for modern bars cleans up to 800 glasses per hour	Capacities	
utomatic detergent injection for consistent results and controlled consumption electable hot and cold rinse for faster turnaround uitable for low pressure areas inse temperature accurately controlled by the nermostop function djustable legs to suit bench requirements implistic visual controls wouble skinned door reducing heat and noise pollution ligh grade stainless steel welded cabinet for durability ustralian made	Loads/Hour Water per Cycle Wash Pump Rinse Pump Wash Tank Litres Rinse Tank Litres Element (wash) Element (rinse) Detergent Injection	up to 60* 6L 310W N.A N.A N.A 20 N.A 3000W yes
	Temperatures	
	Rinse Degrees C	82 - 88 °C
	Plumbing	
	Drain Water	32mm Gravity (Drain pump optional) ½" BSP (cold)
CLUSIONS		½" BSP (hot)
Wire glass rack 17"x14" Water connection hose	Electrical	
Chemical weight & filter Operating manual	Volts/Hz Amps	240V AC/50Hz 15amps
	* Subject to incoming water te	mperature



Water pressure requirements are: 10L/min at 200-400 kPa max.