

RACK CONVEYORS

MADISON IR120







Note: Optional drying unit available

The high powered IR120 rack conveyor speeds through dirty crockery with ease with the ability to complete up to 120 racks per hour!

FEATURES

- Warranty: 1 year parts and labour, 3 years on the control board & cabinet (see p.26 for conditions & extended warranty offer)
- Powerful 10500W wash tank element
- Cleans up to 120 racks per hour
- Double flow wash pump
- Rinse pump to ensure rinse pressure is maintained
- Double skinned door insulation for heat retention
- Ergonomic design
- Recirculating wash system
- 3 wash cycle options
- Three phase power
- Deep drawn tank construction
- Rapid recovery boiler for faster turnaround
- Rinse temperature accurately controlled by the thermostop function
- Easy service access minimising maintenance disruption
- Left and Right hand exit available

INCLUSIONS

- 1 x Plate rack 500mm x 500mm
- 1 x Flat rack 500mm x 500mm
- 1 x Cutlery container
- 1 x Drain hose
- 1 x Water connection hose
- 1 x Operating manual

TECHNICAL DATA	
Height	
Cabinet Cabinet inc. legs With door extended Usable Wash	1420 mm 1585-1645 mm 2055-2115 mm 430 mm
Width	
Cabinet	1150 mm
Depth	
Cabinet	775 mm
Capacities	
Loads/Hour Water per cycle Wash Pump Rinse Pump Wash Tank Litres Rinse Tank Litres Element (wash) Element (rinse) Detergent Injection Rinse Aid Injection	up to 120* 160L/hr 1500W 200W 70 17 10500W 9500W no
Temperatures	
Wash Degrees C Rinse Degrees C	60 °C 82 °C
Plumbing	
Drain Water	Gravity 34" BSP (hot)
Electrical	
Volts/Hz/Phase Amps	400V/50Hz/3+N 40Amps/Ph

^{*} Subject to incoming water temperature



Water pressure requirements are: 10L/min at 200-400 kPa max.